



MOMENTI TORCENTI PER LA REGOLAZIONE DELLE BUSSOLE CON FRIZIONE
TORQUE MOMENTS FOR THE SETTING OF BUSHES WITH FRICTION
COUPLE DE REGLAGE POUR ADAPTEURS À LIMITEUR DE COUPLE
MOMENTO DE TORCION POR LA REGULACION DE LOS PINZA PORTA MACHOS CON
EMBRAGUE

Valori indicativi.

Momento torcente Torque moment Nm	Tipo di filettatura - Threading type									
	Metrico Metric	Withworth	Withworth GAS	BSF	BSP	BA	PG	NPT	UNC	UNF
0,3 0,4 0,5 0,6 0,8	M 2 M 2,5 M 3 M 3,5	1/8"				Nr. 9 Nr. 8 Nr. 7 Nr. 6 Nr. 5			Nr. 2 Nr. 3 Nr. 4	Nr. 2 Nr. 3 Nr. 4 Nr. 5
1 1,2 1,6 2 2,5	M 4 M 5	5/32"		3/16"		Nr. 4 Nr. 3 Nr. 2			Nr. 5 Nr. 6 Nr. 8	Nr. 6 Nr. 8 Nr. 10 Nr. 12
1 4 5 6 8	M 6 M 8	3/16" 7/32" 1/4"	R 1/8"	7/32" 9/32" 5/16"		Nr. 1 Nr. 0			Nr. 10 Nr. 12 1/4"	1/4" 5/16" 3/8"
10 12 16 18 20	M 10	5/16" 3/8"	R 1/4"	3/8" 7/16"	1/8"		PG 7 PG 9	1/8"	5/16" 3/8"	7/16" 1/2" 9/16" 5/8"
22 25 28 32 36	M 12 M 14	7/16" 1/2"	R 3/8"	1/2" 9/16"	1/4" 3/8"		PG 11 PG 13,5 PG 16		7/16" 1/2"	3/4"
40 45 50 56 63	M 16 M 18	9/16" 5/8"	R 1/2" R 5/8"	5/8" 11/16"			PG 21 PG 29	1/4"	5/8"	9/16" 7/8"
70 80 90 100 110	M 20 M 22	3/4" 7/8"	R 3/4" R 7/8"	13/16" 7/8"	1/2" 5/8" 3/4"		PG 36 PG 42 PG 48	3/8"	3/4" 7/8"	1" 1.1/8" 1.1/4" 1.3/8" 1.1/2"
125 140 160 180 200	M 24 M 27	1"	R 1" R 1.1/8" R 1.1/4" R 1.1/8"	1" 1.1/8" 1.1/4"				1/2" 3/4"	1" 1.1/8"	
220 240 260 280 300	M 30 M 33 M 36	1.1/8" 1.1/4"	R 1.1/2" R 1.3/4" R 2" R ---2.1/4"	1.3/8"	1" 1.1/4" 1.1/2"				1.1/4"	
320 340 360 400 420	M 39 M 42	1.3/8" 1.1/2"	1.5/8" R 2.1/2" R 2.3/4" R 3" R 3.1/4"		2"			1"	1.3/8" 1.1/2"	
450 480 500 560 630	M 45 M 48	1.5/8" 1.3/4"	R 3.1/2" R 3.3/4" R 4"	1.3/4" 2"	2.1/2" 3"			1.1/4" 1.1/2"	1.3/4"	
710 800 900 1000 1100	M 52 M 56 M 60 M 64	1.7/8" 2"		2.1/4" 2.1/2" 2.3/4"				2"	2" 2.1/4"	
1250 1400 2000 2200	M 68	2.1/4" 2.1/2" 2.3/4" 3"	3"					2.1/2" 2.1/2"	2.1/2" 2.3/4" 2.3/4"	